

## DECLARATION OF PERFORMANCE

No. : ATS STABLE CORNER HYDRO 700 / 01

**1. Unique identification code of the product type:**

HYDRAULIC ENERGY FIREPLACE ATS STABLE CORNER HYDRO 700

**2. Type, batch or serial number or any other element allowing identification of the construction product, as required by Article 11(4):**

ATS STABLE CORNER HYDRO 700

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

HEATING OF INTERIOR SPACES

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer, as required under Article 11(5):**

THERMIKI AFOI TSALIKI O.E.

MANUFACTURING OF HEATING PRODUCTS

END OF KAPETAN EVKLEIDI, ORAIOKASTRO

THESSALONIKI

Tel. 2310 684595 – FAX. 2310 684595

www.thermiki.gr

Email: info@thermiki.gr

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

—

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

SYSTEM 4

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

EN 13229:2001.

**8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

—

**9. Declared performance:**

| Essential characteristics                          | Performance | Harmonised technical specification |
|----------------------------------------------------|-------------|------------------------------------|
| Nominal heat output                                | 19.56 kW    |                                    |
| Thermal output to water                            | 14.40 kW    |                                    |
| Radiant thermal output                             | 5.16 kW     |                                    |
| Efficiency                                         | 79.00 %     |                                    |
| Average CO concentration at 13% O <sub>2</sub>     | 0.0930 %    |                                    |
| Minimum safety distance from combustible materials | 800 mm      |                                    |
| Average flue gas temperature                       | 223 00b0C   |                                    |

**10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.**

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer by:

.....

(name and position)

**THE DRAFTER**

.....

(place and date of issue)

.....

(signature & company stamp)